



## Handing-Over Certificate – Scaffolding

Contractor \_\_\_\_\_ Date \_\_\_\_\_

Site \_\_\_\_\_ Time \_\_\_\_\_

Description of Section Handed Over \_\_\_\_\_

Drawing Number (where applicable) AAS - \_\_\_\_\_

Physical/Buttress/Hilti Tied [] Ladder [] Rope and Wheel [] \_\_\_\_\_ []

Scaffolding as described above has now been completed and complies with the Construction (Health, Safety and Welfare) Regulations 1996. It is structurally sound and should be used and loaded in accordance with our

Quotation number: \_\_\_\_\_ and your order No: \_\_\_\_\_

If no quotation:

(a) Use only for \_\_\_\_\_

(b) Loading to be 1 number 100% working lifts with a evenly distributed

Load of 2.00 kN/m<sup>2</sup> (lbs/ft<sup>2</sup> per lift)

The detailed requirements of the regulations with regard to guardrails, working platforms, toe-boards, bracing and ties have been complied to British Standards B.S. 5973: 1981 Code of Practice.

This scaffold must be inspected once a week (or following exposure to weather conditions likely to have affected its strength or stability) by the user and the inspection recorded in a suitable register conforming to the Construction (Health, Safety and Welfare) Regulations 1996. This inspection is carried out under regulation 29(1) (2) and is to ensure that the scaffold continues to comply with the regulations.

It is also the responsibility of every employer under the Construction (Health, Safety and Welfare) Regulations 1996 to see that the requirements of the regulations, which apply to his own men, are complied with, see Regulation 3.

N.B. Tarpaulin sheets (or other wind sails) must not be fixed to a scaffold unless it has been specially designed to take them.

(Signed) Approved Representative \_\_\_\_\_ Date \_\_\_\_\_

Certificate received on behalf of contractor

(Signed) Contractor Representative \_\_\_\_\_ (Date if dispatched by post/fax)

Company No 9352724